

## 2.5mm防水耳机插座6PIN板上六脚插板厂家LZG耳机接口音频连接器

产品名称	2.5mm防水耳机插座6PIN板上六脚插板厂家LZG耳机接口音
生产厂家	广东小迈实业有限公司
价格	/
规格参数	品牌:LZG Type-C:6PIN板上2.5mm 特性:防水IPX7
公司地址	东莞市横沥镇西城一区西聚路1号
联系电话	18938295875

### 产品详情

#### 2.5mm防水耳机插座6PIN板上六脚插板厂家LZG耳机接口音频连接器

基本参数：

型号：ZB20002-06DBAP-A

包装：1000/盘



ZB20002-06DBAP-A

**IPX7**

**IP67**

**1A**

**2.5mm**



**防水耳机插座**

致力提供防水连接器解决方案

**防水**





# 防水耳机插座

源头工厂

支持定制

免费拿样



# 防水

ZB20002-06DBAP-A

## 生产厂家 欢迎来访

# 产品应用



汽车领域  
Automotive Electronics Field



数码产品  
Digital Product



电子产品  
Electronics



家用电器  
Household Appliances



通信产品  
Communication Products



影音产品  
Audio and video products



智能家居  
Smart Home



## 专注防水连接器生产制造

## waterproof headphone socket

### ∨ NOTES:

---

1. CURRENT RATING: 1A.
2. CONTACT RESISTANCE: 100mΩ MAX.
3. INSULATION RESISTANCE: 100MΩ MIN.
4. DIELECTRIC WITHSTANDING: 500V AC MIN.
5. DURABILITY: 5000 CYCLES MIN.
6. CONNECTOR MATING FORCES: 3~30N.
7. CONNECTOR UNMATING CORCES: 3~30N.
8. OPERATING TEMPERATURE: -25°C TO +85°C.
9. WATERPROOF LEVEL: IP67.

ISO  
9001:2015

✓  
RoHS

✓ ISO  
14001:2015



**LZG INDUSTRIAL CO.,LTD**










RoHS  
Compliant






ZONE	E.C.N.O.	DESCRIPTION	DRAWING	DATE
A		INITIAL	林生財	2020.02.18

- NOTES
1. CURRENT RATING: 1A
  2. CONTACT RESISTANCE: 100mΩ MAX.
  3. INSULATION RESISTANCE: 100MΩ MIN.
  4. DIELECTRIC WITHSTANDING: 500V AC MIN.
  5. DURABILITY: 5000 CYCLES MIN.
  6. CONNECTOR MATING FORCES: 3~30N.
  7. CONNECTOR UNMATING FORCES: 3~30N.
  8. OPERATING TEMPERATURE: -25°C TO +85°C.
  9. WATERPROOF LEVEL: IP67



Not to install the waterproof ring shipment

NO.	DESCRIPTION	MATERIAL	REMARKS	QTY
10	GLUE	EPOXY	COLOR BLACK	1
9	WATERPROOF RING	SILICONE	COLOR BLACK	1
8	COVER	HIGH TEMPERATURE	COLOR BLACK	1
7	HOUSING	HIGH TEMPERATURE	COLOR BLACK	1
6	TERMINAL 6#	PHOSPHOR BRONZE	NICKEL UNDERPLATING OVERALL, GOLD FLASH PLATING ON THE SOLDER & CONTACT AREA	1
5	TERMINAL 5#	STAINLESS STEEL	NICKEL UNDERPLATING OVERALL, GOLD FLASH PLATING ON THE SOLDER & CONTACT AREA	1
4	TERMINAL 4#	STAINLESS STEEL	NICKEL UNDERPLATING OVERALL, GOLD FLASH PLATING ON THE SOLDER & CONTACT AREA	1
3	TERMINAL 3#	PHOSPHOR BRONZE	NICKEL UNDERPLATING OVERALL, GOLD FLASH PLATING ON THE SOLDER & CONTACT AREA	1
2	TERMINAL 2#	PHOSPHOR BRONZE	NICKEL UNDERPLATING OVERALL, GOLD FLASH PLATING ON THE SOLDER & CONTACT AREA	1
1	TERMINAL 1#	STAINLESS STEEL	NICKEL UNDERPLATING OVERALL, GOLD FLASH PLATING ON THE SOLDER & CONTACT AREA	1



**LZG** LZG INDUSTRIAL CO. LTD

DRAWING:	林生財	DATE:	2020.02.18	SCALE:	1:1
CHECK:	李宏南	DATE:	2020.02.18	MATERIAL:	*
APPROVAL:	林建寬	DATE:	2020.02.18	DWG. NO.:	
DRAWING NO.:	ZB20002-06DBAP-A	SHEET:			1/1

PART NAME	WATERPROOF Ø2.5 PHONE JACK	TOLERANCE UNLESS	0.0±0.25	0.1±2'	UNIT:	mm
PART NO.	ZB20002-06DBAP-A	OTHERWISE SPECIFIED:	0.00±0.20	0.0'±1'		
			0.000±0.10	0.00'±0.5'		