

# 防水TYPE-C母座卧式板上型SMT8Pin防水IPX7充电接口3A厂家LZG

产品名称	防水TYPE-C母座卧式板上型SMT8Pin防水IPX7充电接口3A
生产厂家	广东小迈实业有限公司
价格	/
规格参数	品牌:LZG Type-C:8PIN板上型SMT 特性:防水IPX7
公司地址	东莞市横沥镇西城一区西聚路1号
联系电话	18938295875

## 产品详情

### 防水TYPE-C母座卧式板上型SMT8Pin防水IPX7充电接口3A厂家LZG

产品参数：

型号：ZB48037-08SBAP-A

包装：1000/盘



ZB48037-08SBAP-A

**IPX7**

**IP67**

**3A**



**防水Type-C接口**

致力提供防水连接器解决方案

**防水**





Type-C接口

源头工厂

支持定制

免费拿样



防水

ZB48037-08SBAP-A

生产厂家 欢迎来访

# 产品应用



汽车领域  
Automotive Electronics Field



数码产品  
Digital Product



电子产品  
Electronics



家用电器  
Household Appliances



影音产品  
Audio and video products



通信产品  
Communication Products



智能家居  
Smart Home



## 专注防水连接器生产制造



## waterproof TYPE C serie

### ∨ NOTES:

---

#### 1.ELECTRICAL:

1-1: CURRENT RATING:

VBUS AND GND CONTACTS RATED AT 3A Max.

VBUS AND GND CONTACTS RATED AT 0.5A Min

0.9Amps Max.for all other contact.

PARALLELED FOR A TOTAL OF 5A.

1-2: INITIAL CONTACT RESISTANCE: 40 MEGOHMS.

1-3: DIELECTRIC WITHSTANDING VOLTAGE: 100V AC MIN.

#### 2: MECHANICAL CHARACTERISTICS:

2-1: MATING FORCE: 5~20N.

2-2: UNMATING FORCE: 8~20N(INITIAL),

6~20N(AFTER 10000 CYCLES).

2-3: FREQUENCY: 200±50 CYCLES/HOUR,10000 CYCLES

ISO  
9001:2015

✓  
RoHS



✓ ISO  
14001:2015



**LZG INDUSTRIAL CO.,LTD**

RoHS  
Compliant

ZONE	ECN.NO.	DESCRIPTION	DRAWING	DATE
A		INITIAL	林生淵	2020.02.18



3D VIEW

SPECIFICATIONS:

1.ELECTRICAL:

1-1:CURRENT RATING:

VBUS AND GND CONTACTS RATED AT 3A Max  
VBUS AND GND CONTACTS RATED AT 0.5A Min  
0.9Amps Max.for all other contact.  
PARALLELED FOR A TOTAL OF 5A;

1-2:INITIAL CONTACT RESISTANCE:40 MEGOHMS

1-3:DIELECTRIC WITHSTANDING VOLTAGE:100V AC MIN;

2:MECHANICAL CHARACTERISTICS:






2-1:MATING FORCE:5~20N

2-2:UNMATING FORCE:8~20N(INITIAL),6~20N(AFTER 10000 CYCLES)

2-3:FREQUENCE:200±50 CYCLES/HOUR,10000 CYCLES

2-4:OPERATING TEMPERATURE:-40°~80°.

3:WATERPROOF:IP-X5.



Type c Pin Assignments

PIN	SIGNAL NAME	PIN	SIGNAL NAME	no.	DESCRIPTION	MATERIAL	REMARKS	QTY
A5	CC1			4	LATCH	STAINLESS STEEL		1
A6	DP1			3	SHELL	ZINC ALLOY	MATTE NICKEL PLATING	1
A7	DN1	B12	GND	2	CONTACT	COPPER ALLOY	GOLD PLATING	8
A9	VBUS	B9	VBUS	1	HOUSING	HIGH TEMPERATURE PLASTIC 94V-0	COLOR BLACK	1
A12	GND	B5	CC2					

**LZG**

LZG INDUSTRIAL CO. LTD

DRAWING:	林生淵	DATE:	2020.02.18	SCALE	1:1
CHECK:	林生淵	DATE:	2020.02.18	MATERIAL	*
APPROVAL:	林生淵	DATE:	2020.02.18	DWG. NO.	
DRAWING NO.	ZB48037-08SBAP-A	SHEET	1/2		

PART NAME	WATERPROFF TYPE C BPIN	TOLERANCE UNLESS OTHERWISE SPECIFIED:	0.04±0.3 0.00±0.1 0.000±0.05	0.°±2° 0.0°±1° 0.00°±0.5°	UNIT: mm
PART NO.	ZB48037-08SBAP-A				

# 企业优势

防水DC插座、防水耳机插座  
QUALIFICATION DISPLAY

01  
企业  
品牌

精密防水耳机插座实体工厂  
十余年行业经验



交期快、打样和做货速度快  
大量现货、供应需求0压力

02  
现货  
库存



03  
品质  
服务

高效的服务团队、专注的客服团队  
售前售后服务保障





