

防水TYPE-C母座卧式板上型SMT3柱16Pin防水IPX7充电接口3A厂家LZG

产品名称	防水TYPE-C母座卧式板上型SMT3柱16Pin防水IPX7充电接口
生产厂家	广东小迈实业有限公司
价格	/
规格参数	品牌:LZG Type-C:16pin板上3A带柱 特性:防水IPX7
公司地址	东莞市横沥镇西城一区西聚路1号
联系电话	18938295875

产品详情

防水TYPE-C母座卧式板上型SMT3柱16Pin防水IPX7充电接口3A厂家LZG

产品详情：

型号：ZB48030-16FBAP-A

包装：1500/盘



ZB48030-16FBAP-A

IPX7
IP67
5A



防水Type-C接口

致力提供防水连接器解决方案

防水





Type-C接口

源头工厂

支持定制

免费拿样



防水

ZB48030-16FBAP-A

生产厂家 欢迎来访

产品应用



汽车领域
Automotive Electronics Field



数码产品
Digital Product



电子产品
Electronics



家用电器
Household Appliances



影音产品
Audio and video products



通信产品
Communication Products



智能家居
Smart Home



专注防水连接器生产制造



waterproof TYPE C serie

✓ NOTES:

1. ELECTRICAL:

1.1. CONTACT CURRENT RATING 5.0A FOR
VBUS AND GND(PINS A4 A9 B4 B9)

1.2. INSULATION RESISTANCE: 100 MEGAOHMS MIN. AT 250VDC.

1.3. DIELECTRIC WITHSTANDING VOLTAGE: 100VAC MIN.

1.4. LOW CONTACT RESISTANCE:

INITIAL 40mΩ MAX. AFTER 50mΩ MAX.

2. MECHANICAL CHARACTERISTICS:

2.1. INSERTION FORCE: 5N~20N.

2.2. EXTRACTION FORCE: 8N~20N FORM 1 TO 1000CYCLES.
6~20N FORM 1001 TO 10000CYCLES.

2.3. DURABILITY: 10,000 MATING CYCLES

2.4. OPERATING TEMPERATURE: -55°C TO +85°C

ISO
9001:2015

✓
RoHS

✓ ISO
14001:2015



LZG INDUSTRIAL CO.,LTD



RoHS
Compliant

ZONE	EC N. NO.	DESCRIPTION	DRAWING	DATE
A		INITIAL	林生財	2020.02.18




SPECIFICATIONS:





1. ELECTRICAL:
 - 1.1. CONTACT CURRENT RATING 5.0A FOR VBUS AND GND(PINS A4 A9 B4 B9)
 - 1.2. INSULATION RESISTANCE: 100 MEGAOHMS MIN. AT 250VDC.
 - 1.3. DIELECTRIC WITHSTANDING VOLTAGE: 100VAC MIN.
 - 1.4. LOW CONTACT RESISTANCE: INITIAL 40mΩ MAX. AFTER 50mΩ MAX.
2. MECHANICAL CHARACTERISTICS:
 - 2.1. INSERTION FORCE: 5N~20N.
 - 2.2. EXTRACTION FORCE: 8N~20N FORM 1 TO 1000CYCLES. 6~20N FORM 1001 TO 10000CYCLES.
 - 2.3. DURABILITY: 10,000 MATING CYCLES
 - 2.4. OPERATING TEMPERATURE: -55°C TO +85°C
3. COPLANARITY: 0.08MAX.
4. INSPECTION SYMBOL: IMPORTANCE INSPECTION.
5. Waterproof Level: IPX8



TYPE-C 16P 5.4L



TYPE-C 16P 6.5L



Type c Pin Assignments

PIN	SIGNAL NAME	PIN	SIGNAL NAME
A1	GND	B12	GND
A2		B11	
A3		B10	
A4	VBUS	B9	VBUS
A5	CC1	B8	SBX2
A6	Dn1	B7	Dn2
A7	Dn1	B6	Dn2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10		B3	
A11		B2	
A12	GND	B1	GND

NO.	DESCRIPTION	MATERIAL	REMARKS	QTY
6	RUBBER RING	SILICA GEL	COLOR BLACK	1
5	BOTTOM CONTACT	COPPER ALLOY	SEE NOTES	8
4	TOP CONTACT	COPPER ALLOY	SEE NOTES	8
3	Mid-PLATE	STAINLESS STEEL	NICKEL PLATED 50u" MIN. OVER ALL	1
2	INSERT HOUSING	LOP 94W-0	COLOR BLACK	1
1	SHELL	STAINLESS STEEL	NICKEL PLATED 50u" MIN. OVER ALL	1

LZG LZG INDUSTRIAL CO. LTD

DRAWING:	林生財	DATE:	2020.02.18	SCALE:	1:1
CHECK:	李宏康	DATE:	2020.02.18	MATERIAL:	*
APPROVAL:	劉建堂	DATE:	2020.02.18	DWG. NO.:	
DRAWING NO.:	ZB48030-16FBAP-A			SHEET:	1/2

PART NAME	WATERPROFF TYPE C 16 PIN	TOLERANCE UNLESS	0.0±0.38	0.1±2'	UNIT:	mm
PART NO.	ZB48030-16FBAP-A	OTHERWISE SPECIFIED:	0.00±0.25 0.000±0.13	0.0'±1'		