

防水TYPE-C母座卧式板上型双排24Pin防水IPX7充电接口3A厂家LZG

产品名称	防水TYPE-C母座卧式板上型双排24Pin防水IPX7充电接口3A
生产厂家	广东小迈实业有限公司
价格	/
规格参数	品牌:LZG Type-C:24pin板上双排3A 特性:防水IPX7
公司地址	东莞市横沥镇西城一区西聚路1号
联系电话	18938295875

产品详情

防水TYPE-C母座卧式板上型双排24Pin防水IPX7充电接口3A厂家LZG

产品参数：

型号：ZB48029-24SBAP-A

包装：800/盘



ZB48029-24SBAP-A

IPX7
IP67
3A



防水Type-C接口

致力提供防水连接器解决方案

防水





Type-C接口

源头工厂

支持定制

免费拿样



防水

ZB48029-24SBAP-A

生产厂家 欢迎来访

产品应用



汽车领域
Automotive Electronics Field



数码产品
Digital Product



电子产品
Electronics



家用电器
Household Appliances



影音产品
Audio and video products



通信产品
Communication Products



智能家居
Smart Home



专注防水连接器生产制造



waterproof TYPE C serie

✓ NOTES:

1. ELECTRICAL CHARACTERISTICS:

1-1. CONTACT CURRENT RATING:

5.0A FOR VBUS PIN AND ITS CORRESPONDING GND PIN.

1-2. CONTACT RESISTANCE:

30 MILLIOHMS MAX FOR VBUS AND GND CONTACTS.

40 MILLIOHMS MAX FOR ALL OTHER CONTACTS.

1-3. DIELECTRIC WITHSTANDING VOLTAGE: 100 VRMS AC MIN.

1-4. INSULATION RESISTANCE: 100 MEGOHMS MIN.

2. MECHANICAL CHARACTERISTICS:

2-1. CONNECTOR INSERTION FORCE: 5~20N.

AT A MAXIMUM RATE OF 12.5MM PER MINUTE.

2-2. CONNECTOR EXTRACTION FORCE:

8~20N AT A MAXIMUM RATE OF 12.5MM PER MINUTE.

6~20N AFTER DURABILITY TEST.

ISO
9001:2015

✓
RoHS

✓ ISO
14001:2015



LZG INDUSTRIAL CO.,LTD

