

3.5mm防水耳机插座5PIN五脚插板1A音频接口母座IPX7厂家LZG

产品名称	3.5mm防水耳机插座5PIN五脚插板1A音频接口母座IPX7厂家
生产厂家	广东小迈实业有限公司
价格	/
规格参数	品牌:LZG 音频接口:5Pin插板1A母座 特性:防水IPX7
公司地址	东莞市横沥镇西城一区西聚路1号
联系电话	18938295875

产品详情

3.5mm防水耳机插座5PIN五脚插板1A音频接口母座IPX7厂家LZG

基本参数：

型号：ZB23017-05DBAP-A

包装：700/盘

3.5MM防水耳机插座，防水等级IPx7,产品可兼容CUI ADM TIC等品牌产品。



ZB23017-05DBAP-A

IPX7
IP67
1A
3.5mm



防水耳机插座

致力提供防水连接器解决方案

防水





防水耳机插座

源头工厂

支持定制

免费拿样



防水

ZB23017-05DBAP-A

生产厂家 欢迎来访

产品应用



汽车领域
Automotive Electronics Field



数码产品
Digital Product



电子产品
Electronics



家用电器
Household Appliances



影音产品
Audio and video products



通信产品
Communication Products



智能家居
Smart Home



专注防水连接器生产制造



waterproof headphone socket

✓ NOTES:

1. CURRENT RATING: 1A.
2. CONTACT RESISTANCE: 100mΩ MAX.
3. INSULATION RESISTANCE: 100MΩ MIN.
4. DIELECTRIC WITHSTANDING: 500V AC MIN.
5. DURABILITY: 5000 CYCLES MIN.
6. CONNECTOR MATING FORCES: 3~30N.
7. CONNECTOR UNMATING FORCES: 3~30NX.
8. SALT SPRAY: 24HOUR
9. WATERPROOF LEVEL: IP67.
10. OPERATING TEMPERATURE: -25°C TO +85°C.

ISO
9001:2015

✓
RoHS

✓ ISO
14001:2015




LZG INDUSTRIAL CO.,LTD

RoHS
Compliant






ZONE	EC.N.O.	DESCRIPTION	DRAWING	DATE
A		INITIAL	林生財	2020.02.18


- NOTES
- CURRENT RATING: 1A
 - CONTACT RESISTANCE: 100mΩ MAX.
 - INSULATION RESISTANCE: 100MΩ MIN.
 - DIELECTRIC WITHSTANDING: 500V AC MIN.
 - DURABILITY: 5000 CYCLES MIN.
 - CONNECTOR MATING FORCES: 3~30N.
 - CONNECTOR UNMATING FORCES: 3~30NX.
 - SALT SPRAY: 24HOUR
 - WATERPROOF LEVEL: IP67.
 - OPERATING TEMPERATURE: -25°C TO +85°C.



3D VIEW






PCB LAYOUT (TOP VIEW)
TOLERANCE: ±0.05



Not to install the waterproof ring shipment

NO.	DESCRIPTION	MATERIAL	REMARKS	QTY
9	GLUE	EPOXY	COLOR BLACK	1
8	WATERPROOF RING	SILICONE	COLOR BLACK	1
7	HOUSING	HIGH TEMPERATURE	COLOR BLACK	1
6	COVER	HIGH TEMPERATURE	COLOR BLACK	1
5	TERMINAL 5#	STAINLESS STEEL	NICKEL UNDERPLATING OVERALL, GOLD FLASH PLATING ON THE SOLDER & CONTACT AREA	1
4	TERMINAL 4#	STAINLESS STEEL	NICKEL UNDERPLATING OVERALL, GOLD FLASH PLATING ON THE SOLDER & CONTACT AREA	1
3	TERMINAL 3#	PHOSPHOR BRONZE	NICKEL UNDERPLATING OVERALL, GOLD FLASH PLATING ON THE SOLDER & CONTACT AREA	1
2	TERMINAL 2#	PHOSPHOR BRONZE	NICKEL UNDERPLATING OVERALL, GOLD FLASH PLATING ON THE SOLDER & CONTACT AREA	1
1	TERMINAL 1#	STAINLESS STEEL	NICKEL UNDERPLATING OVERALL, GOLD FLASH PLATING ON THE SOLDER & CONTACT AREA	1



BLACK WATERPROOF RING

LZG

LZG INDUSTRIAL CO. LTD

DRAWING:	林生財	DATE:	2020.02.18	SCALE:	1:1
CHECK:	李安倫	DATE:	2020.02.18	MATERIAL:	*
APPROVAL:	魏建寶	DATE:	2020.02.18	DWG. NO.:	
DRAWING NO.:	ZB23017-05DBAP-A	SHEET:			1/1

PART NAME	TOLERANCE UNLESS OTHERWISE SPECIFIED:	0.0±0.25	0.1±0.15	0.2±0.1	UNIT:	mm
PART NO.	ZB23017-05DBAP-A	0.000±0.10	0.0'±2'	0.0'±1'		