

3.5mm防水耳机插座5PIN音频接头五脚母座板上厂家LZG接口12V0.5A

产品名称	3.5mm防水耳机插座5PIN音频接头五脚母座板上厂家LZG接
生产厂家	广东小迈实业有限公司
价格	/
规格参数	品牌:LZG 音频接口:5脚板上12V0.5A 特性:防水IPX7
公司地址	东莞市横沥镇西城一区西聚路1号
联系电话	18938295875

产品详情

3.5mm防水耳机插座5PIN音频接头五脚母座板上厂家LZG接口12V0.5A

基本参数：

型号：ZB23007-05DBAP-A

包装：500/盘

3.5MM防水耳机插座，防水等级IPx7,产品可兼容CUI ADM TIC等品牌产品



ZB23007-05DBAP-A

IPX7

IP67

1A

3.5mm



防水耳机插座

致力提供防水连接器解决方案

防水





防水耳机插座

源头工厂

支持定制

免费拿样



防水

ZB23007-05DBAP-A

生产厂家 欢迎来访

产品应用



汽车领域
Automotive Electronics Field



数码产品
Digital Product



电子产品
Electronics



家用电器
Household Appliances



通信产品
Communication Products



影音产品
Audio and video products



智能家居
Smart Home



专注防水连接器生产制造

waterproof headphone socket

✓ NOTES:

1. CURRENT RATING: 1A.
2. CONTACT RESISTANCE: 100mΩ MAX.
3. INSULATION RESISTANCE: 100MΩ MIN.
4. DIELECTRIC WITHSTANDING: 500V AC MIN.
5. DURABILITY: 5000 CYCLES MIN.
6. CONNECTOR MATING FORCES: 3~30N.
7. CONNECTOR UNMATING CORCES: 3~30N.
8. OPERATING TEMPERATURE: -25°C TO +85°C.
9. WATERPROOF LEVEL: IP67

ISO
9001:2015

✓
RoHS



✓ ISO
14001:2015



LZG INDUSTRIAL CO.,LTD



RoHS
Compliant






3D VIEW






ZONE	ECN.N.O.	DESCRIPTION	DRAWING	DATE
A		INITIAL	林建賢	2020.02.18

NOTES

1. CURRENT RATING: 1A.
2. CONTACT RESISTANCE: 100mΩ MAX.
3. INSULATION RESISTANCE: 100MΩ MIN.
4. DIELECTRIC WITHSTANDING: 500V AC MIN.
5. DURABILITY: 5000 CYCLES MIN.
6. CONNECTOR MATING FORCES: 3~30N.
7. CONNECTOR UNMATING FORCES: 3~30N.
8. OPERATING TEMPERATURE: -25°C TO +85°C.
9. WATERPROOF LEVEL: IP67



PCB LAYOUT (TOP VIEW)
TOLERANCE: ±0.05



NO.	DESCRIPTION	MATERIAL	REMARKS	QTY
8	GLUE	EPOXY	COLOR BLACK	1
7	COVER	HIGH TEMPERATURE	COLOR BLACK	1
6	HOUSING	HIGH TEMPERATURE	COLOR BLACK	1
5	TERMINAL 5#	STAINLESS STEEL	NICKEL UNDERPLATING OVERALL, GOLD FLASH PLATING ON SOLDER & CONTACT AREA	1
4	TERMINAL 4#	STAINLESS STEEL	NICKEL UNDERPLATING OVERALL, GOLD FLASH PLATING ON SOLDER & CONTACT AREA	1
3	TERMINAL 3#	STAINLESS STEEL	NICKEL UNDERPLATING OVERALL, GOLD FLASH PLATING ON SOLDER & CONTACT AREA	1
2	TERMINAL 2#	STAINLESS STEEL	NICKEL UNDERPLATING OVERALL, GOLD FLASH PLATING ON SOLDER & CONTACT AREA	1
1	TERMINAL 1#	STAINLESS STEEL	NICKEL UNDERPLATING OVERALL, GOLD FLASH PLATING ON SOLDER & CONTACT AREA	1



LZG INDUSTRIAL CO. LTD

PART NAME	WATERPROOF 83.5 PHONE JACK	TOLERANCE UNLESS OTHERWISE SPECIFIED:	0.0±0.25 0.00±0.15 0.000±0.10	0.°±2° 0.0°±1° 0.00°±0.5°	UNIT: mm		APPROVAL: 林建賢	DATE: 2020.02.18	SCALE: 1:1	MATERIAL: *
PART NO.	ZB23007-05DBAP-A						DRAWING NO.	ZB23007-05DBAP-A	SHEET	1/1

DRAWING:	林建賢	DATE:	2020.02.18	SCALE:	1:1
CHECK:	林建賢	DATE:	2020.02.18	MATERIAL:	*
APPROVAL:	林建賢	DATE:	2020.02.18	DWG. NO.:	
DRAWING NO.:	ZB23007-05DBAP-A	SHEET:			1/1