

防水DC插座9Pin板上九脚插板LZG厂家DC电源插座20V10A防水IPX7

产品名称	防水DC插座9Pin板上九脚插板LZG厂家DC电源插座20V10A
生产厂家	广东小迈实业有限公司
价格	/
规格参数	品牌:LZG DC母座:9Pin板上20V10A 特性:防水IPX7
公司地址	东莞市横沥镇西城一区西聚路1号
联系电话	18938295875

产品详情

防水DC插座9Pin板上九脚插板LZG厂家DC电源插座20V10A防水IPX7

型号：ZB30009-09DBAP-A

插座类型：DC插座，电镀工艺：镀金，额定电压：20V



ZB30009-09DBAP-A

IPX7

IP67

20V/10A



防水DC插座

致力提供防水连接器解决方案

防水



IZG[®]



ZB30009-09DBAP-A

防水DC插座

产品应用

IZG



汽车电子
Automotive Electronics



扩展坞、路由器
Docking Station, Router



通讯设备
Communication Equipment



家用电器
Household Appliances



蓝牙音响、家庭音响
Bluetooth Audio, Home Audio



安防监控
Security Monitoring



智能家居
Smart Home



专注防水连接器生产制造



waterproof DC socket

∨ NOTES:

1. ELECTRICAL CHARACTERISTICS:

1-1. RATING: 20V 10A

1-2. CONTACT RESISTANCE: 30m MAX.(INITIAL)

1-3. DIELECTRIC WITHSTANDING VOLTAGE:

500V AC FOR ONE MINUTE.

1-4. INSULATION RESISTANCE: 100M MIN. MEASURED
BY 250 VDC.

2. MECHANICAL CHARACTERISTICS:

2-1. INSERTION FORCE : 3.0 KGF Max.

2-2. WITHDRAWAL FORCE : 0.30 KGF Min.

3. LIFE TEST: 5,000 CYCLES MIN.

4. TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE
FREE SPEC.

ISO
9001:2015

✓
RoHS

✓ ISO
14001:2015





LZG INDUSTRIAL CO.,LTD

RoHS
Compliant







ZONE	EC N. NO	DESCRIPTION	DRAWING	DATE
A		INITIAL	林生財	2020.02.18



SPECIFICATIONS:
 1. ELECTRICAL CHARACTERISTICS:
 1-1. RATING: 20V 10A
 1-2. CONTACT RESISTANCE: 30mΩ MAX.(INITIAL)
 1-3. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE.
 1-4. INSULATION RESISTANCE: 100MΩ MIN. MEASURED BY 250 VDC
 2. MECHANICAL CHARACTERISTICS:
 2-1. INSERTION FORCE : 3.0 KGF Max.
 2-2. WITHDRAWAL FORCE : 0.30 KGF Min.
 3. LIFE TEST: 5,000 CYCLES MIN.
 4. TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.




3D VIEW




RECOMMENDED P.C.B LAYOUT
TOP VIEW (TOLERANCE:±0.05)



SECTION A-A
SCALE 1:1



MATING PLUG: OD Ø7.4 ; ID Ø0.6
Tolerance:±0.05



防水蓋

7	Rubber ring	Silica Gel	COLOR BLACK	1
6	Shell	Brass 0.25t	Ni Plating overall	1
5	SIGNAL (S)	Phosphor bronze, 0.30t	Ag Plating overall	1
4	CONTACT (+)	Phosphor bronze, 0.30t	Ag Plating overall	1
3	SPRING (-)	Phosphor bronze, 0.30t	Ag Plating overall	1
2	Cover	HIGH TEMPERATURE PLASTIC	COLOR BLACK	1
1	Housing	HIGH TEMPERATURE PLASTIC	COLOR BLACK	1
NO.	DESCRIPTION	MATERIAL	REMARKS	QTY



LZG INDUSTRIAL CO., LTD

DRAWING:	林生財	DATE:	2020.02.18	SCALE:	1:1
CHECK:	李宏鑫	DATE:	2020.02.18	MATERIAL:	*
APPROVAL:	翁进宝	DATE:	2020.02.18	DWG. NO.	
DRAWING NO.	ZB30009-09DBAP-A			SHEET	1/1

PART NAME	DC POWER JACK	TOLERANCE UNLESS	0.0±0.3	0.°±2'	UNIT:	mm
PART NO.	ZB30009-09DBAP-A	OTHERWISE SPECIFIED:	0.00±0.25 0.000±0.2	0.0'±1'		