

防水DC电源插座3Pin三脚带柱厂家LZG直流DC充电插座24V5A防水IPX7

产品名称	防水DC电源插座3Pin三脚带柱厂家LZG直流DC充电插座24V
生产厂家	广东小迈实业有限公司
价格	/
规格参数	品牌:LZG DC母座:3pin插板5A24V 特性:防水IPX7
公司地址	东莞市横沥镇西城一区西聚路1号
联系电话	18938295875

产品详情

防水DC电源插座3Pin三脚带柱厂家LZG直流DC充电插座24V5A防水IPX7

型号：ZB30008-03DBAP-A

插座类型：DC插座，电镀工艺：镀金，额定电压：24V，额定电流：5A，MPQ：250PCS/盘



ZB30008-03DBAP-A

IPX7

IP67

24V/5A



防水DC插座

致力提供防水连接器解决方案

防水



IZG[®]



ZB30008-03DBAP-A

防水DC插座（2.0针）

产品应用



汽车电子
Automotive Electronics



扩展坞、路由器
Docking Station, Router



通讯设备
Communication Equipment



家用电器
Household Appliances



安防监控
Security Monitoring



蓝牙音响、家庭音响
Bluetooth Audio, Home Audio



智能家居
Smart Home



专注防水连接器生产制造



waterproof DC socket

∨ NOTES:

1. CURRENT RATING: 24V & 5A MAX.
2. CONTACT RESISTANCE: 50mΩ MAX.
3. INSULATION RESISTANCE: 100MΩ MIN.
4. DIELECTRIC WITHSTANDING: 500V AC MIN.
5. DURABILITY: 5000 CYCLES MIN.
6. CONNECTOR MATING FORCES: 3N MIN.
7. CONNECTOR UNMATING FORCES: 35N MAX.
8. OPERATING TEMPERATURE: -25°C TO +85°C.
9. WATER PROOFNESS: THIS PRODUCT IS BASED ON IPX7.

ISO
9001:2015

✓
RoHS



✓ ISO
14001:2015



LZG INDUSTRIAL CO.,LTD

RoHS
Compliant

1#(+)
2#(S)
3#(-)







3D VIEW






ZONE	ECN. NO.	DESCRIPTION	DRAWING	DATE
A		INITIAL	製	2020.02.18

NOTES


1. CURRENT RATING: 24V & 5A MAX.
2. CONTACT RESISTANCE: 50mΩ MAX.
3. INSULATION RESISTANCE: 100MΩ MIN.
4. DIELECTRIC WITHSTANDING: 500V AC MIN.
5. DURABILITY: 5000 CYCLES MIN.
6. CONNECTOR MATING FORCES: 3N MIN.
7. CONNECTOR UNMATING FORCES: 35N MAX.
8. OPERATING TEMPERATURE: -25°C TO +85°C.
9. WATER PROOFNESS: THIS PRODUCT IS BASED ON IPX7.



POB LAYOUT (TOP VIEW)
TOLERANCE: ±0.05



WHITE WATERPROOF RING



Not to install the waterproof ring shipment

NO.	DESCRIPTION	MATERIAL	REMARKS	QTY
7	WATERPROOF RING	SILICONE	WHITE	1
6	GLUE	EPOXY	COLOR BLACK	1
5	BACK COVER	HIGH TEMPERATURE	COLOR BLACK	1
4	HOUSING	HIGH TEMPERATURE	COLOR BLACK	1
3	TERMINAL 3#	COPPER ALLOY	NICKEL UNDERPLATING OVERALL, Au PLATING ON THE SOLDER AREA	1
2	TERMINAL 2#	COPPER ALLOY	NICKEL UNDERPLATING OVERALL, Au PLATING ON THE WHOLE	1
1	CENTER PIN 1#	COPPER ALLOY	NICKEL UNDERPLATING OVERALL, Au PLATING ON THE SOLDER AREA	1



LZG INDUSTRIAL CO. LTD

DRAWING:	製	DATE:	2020.02.18	SCALE:	1:1
CHECK:	製	DATE:	2020.02.18	MATERIAL:	*
APPROVAL:	製	DATE:	2020.02.18	DWG. NO.:	
DRAWING NO.:	ZB30008-03DBAP-A			SHEET:	1/1

PART NAME	Ø2.0 DC WATERPROOF POWER JACK
PART NO.	ZB30008-03DBAP-A

TOLERANCE UNLESS OTHERWISE SPECIFIED:	0.0±0.30	0.4±0.2
	0.00±0.20	0.0±0.1
	0.000±0.10	0.00±0.5

UNIT:	mm
-------	----